

## Wafer Tip EPDM Contalı Kelebek Vana



### ÖZELLİKLER

Gövde (1)	GGG40
Conta (2)	EPDM
Mil (3)	SS416
Klape (4)	CF8-CF8M
Burç (5)	PTFE
O-ring (6)	NBR
Kol (7)	Alüminyum
Çalışma Sıcaklığı	-15 °C / +80 °C
Basınç Sınıfı	PN16

### BOYUTLAR

ÖLÇÜ	A	B	H	P	C	ISO 5211	LO	T	L	Flanş	
										PN10	PN16
DN40	125	68	30	9	33	F05	215	137	150	110	110
DN50	129	73	30	9	42	F05	215	137	150	125	125
DN65	137	82	30	9	44,7	F05	215	137	150	145	145
DN80	144	95	30	9	45,2	F05	215	137	150	160	160
DN100	163	109	30	11	52,1	F07	260	137	150	180	180
DN125	179	125	30	14	54,4	F07	260	137	150	210	210
DN150	198	144	30	14	55,8	F07	260	137	150	240	240
DN200	237	173	35	17	60,8	F10	355	269	207	295	295
DN250	281	211	35	22	65,8	F10	355	269	207	350	355
DN300	318	244	35	22	76,9	F10	355	269	207	400	410
DN350	310	260	40	27	78	F10	-	300	201	460	470
DN400	340	315	40	27	102	F14	-	300	230	515	525

