

3 Parçalı Dişli Küresel Vana



ÖZELLİKLER

Gövde	AISI304 / AISI316
Küre	AISI304 / AISI316
Conta	PTFE
Küre Mili	AISI304 / AISI316
Mil Somunu	AISI304
Mil Rakoru	AISI304
Kol	AISI304
Kilit Mekanizması	AISI304
Çalışma Sıcaklığı	-30 °C / +120 °C
Basınç Sınıfı	PN63

BOYUTLAR

SINIF	ÖLÇÜ	L	Kb	H	Ød	Ødü	ØDd	ØDb
PN40	DN15 1/2"	75	120	65	15	18,6	21	15
PN40	DN20 3/4"	80	140	70	20	24,2	26,4	16
PN40	DN25 1"	90	145	80	25	30,2	33,2	19
PN40	DN32 1.1/4"	110	160	85	32	39	41,9	21
PN40	DN40 1.1/2"	120	160	100	40	44,9	47,8	21
PN40	DN50 2"	140	205	105	50	56,7	59,6	25
PN16	DN65 2.1/2"	185	300	145	65	72,2	75,2	30
PN16	DN80 3"	205	410	180	80	84,9	87,9	33
PN16	DN100 4"	240	410	195	100	110	113	35

