

Lug Tipi Teflon Contalı Kelebek Vana



ÖZELLİKLER

Gövde	GGG40
Conta	PTFE
Mil	SS416
Klape	CF8-CF8M
Burç	PTFE
O-Ring	NBR
Kol	Alüminyum
Çalışma Sıcaklığı	-10 °C / +120 °C
Basınç Sınıfı	PN16

BOYUTLAR

ÖLÇÜ	A	B	H	P	C	ISO 5211	LO	T	L	Flanş	
										PN16	
DN40	125	68	30	9	33	F05	215	137	150	110	4-M16
DN50	129	73	30	9	42	F05	215	137	150	125	4-M16
DN65	137	82	30	9	44,7	F05	215	137	150	145	4-M16
DN80	144	95	30	9	45,2	F05	215	137	150	160	8-M20
DN100	163	109	30	11	52,1	F07	260	137	150	180	8-M20
DN125	179	125	30	14	54,4	F07	260	137	150	210	8-M20
DN150	198	144	30	14	55,8	F07	260	137	150	240	8-M20
DN200	237	173	35	17	60,8	F10	355	269	207	295	8-M20
DN250	281	211	35	22	65,8	F10	355	269	207	355	12-M24
DN300	318	244	35	22	76,9	F10	355	269	207	410	12-M24
DN350	368	267	45	24	76,5	F10	-	269	195	470	16-M24
DN400	400	309	51,5	24	86,5	F14	-	290	243	525	16-M27

